NSN 5305-01-044-3006

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-044-3006 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.438 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas1191 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-044-3006

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0