## NSN 5305-01-044-4417

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-044-4417
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.307 inches and 0.357 inches
Fastener Length:
Between 1.478 inches and 1.498 inches
Head Style:
Crowned hexagon
Head Height:
Between 0.157 inches and 0.172 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Locking Feature:
Detent ball grip
Grip Diameter:
Between 0.3112 inches and 0.3117 inches
Shank Unthreaded Hole Diameter:
0.076 inches and 0.086 inches first hole
Internal Drive Style:
Slot
Thread Diameter:
0.312 inches
Grip Length:
Between 1.000 inches and 1.016 inches
Thready Qty Per Inch (tpi):
24
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.365 inches and 1.385 inches first hole
Surface Finish:
32.0 microinches grip
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5305-01-044-4417

Close Tolerance Screw - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0