## NSN 5305-01-044-5206

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-044-5206 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 1.735 inches and 1.782 inches **Head Style:** Round **Head Diameter:** 0.593 inches **Head Height:** Between 0.162 inches and 0.183 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** Between 39.0 rockwell c and 43.0 rockwell c **Screw Material:** Steel comp 4340 or steel comp 4140 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification all treatment responses **Shank Surface Finish:** 8.0 microinches **Thread Series Designator:** Unf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-01-044-5206

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.