NSN 5305-01-044-5207



SN 3303-01-044-3207 chine Screw - Page 1 of 2	AGTUDA Gr
v Online at https://aerobasegroup.com/nsn/5305-01-044-5207	
ad Class:	
ad Direction:	
t-hand	
ead Length:	
5 inches	
ener Length:	
veen 1.610 inches and 1.657 inches	
d Style:	
nd	
d Diameter:	
3 inches	
d Height:	
veen 0.162 inches and 0.183 inches	
nal Drive Style:	
ue set	
ad Diameter:	
2 inches	
eady Qty Per Inch (tpi):	
Tensile Strength (psi):	
000 pounds per square inch	
Iness Rating:	
veen 39.0 rockwell c and 43.0 rockwell c	
w Material:	
l comp 4340 or steel comp 4140 or steel comp 8740	
w Material Specification:	
-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or	⁻ mil-s-6049 military
ification 3rd material response	
ew Surface Treatment:	
mium and chromate	
ew Surface Treatment Specification:	
o-416 type 2 cl 2 federal specification all treatment responses	
nk Surface Finish:	
microinches	
ead Series Designator:	
If Life:	
Of Measure:	
ilitarization:	

NSN 5305-01-044-5207

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5000 spec.

