## NSN 5305-01-045-2468

**Thread Class:** 

**Thread Direction:** 

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-045-2468

Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 1.199 inches and 1.229 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.328 inches and 0.385 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1153 professional/industrial association standard
Shelf Life:
N/a

## NSN 5305-01-045-2468

Close Tolerance Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0