NSN 5305-01-045-2539

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-045-2539 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.372 inches and 0.422 inches **Fastener Length:** Between 0.632 inches and 0.662 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.421 inches and 0.426 inches **Shoulder Diameter:** 0.249 inches first shoulder and 0.2495 inches first shoulder **Shoulder Length:** 0.176 inches first shoulder and 0.204 inches first shoulder **Internal Drive Style:** High-torque **End Application:** Fms - aircraft, hornet f/a-18; aircraft, eagle f-15; aircraft, hornet f/a-18; aircraft, harrier av-8b **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Socket drive recess in thread end 0.095 inch width across flats Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-045-2539

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0