

View Online at <https://aerobasegroup.com/nsn/5305-01-045-3018>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.306 inches and 0.356 inches

Fastener Length:

Between 1.191 inches and 1.221 inches

Head Style:

Oval countersunk

Head Diameter:

Between 0.328 inches and 0.333 inches

Shoulder Diameter:

0.2177 inches first shoulder and 0.2182 inches first shoulder

Shoulder Length:

0.815 inches first shoulder and 0.843 inches first shoulder

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Shoulder Shape:

Round first shoulder

Special Features:

Socket drive recess in thread end 0.0791 in. Min and 0.0806 in. Maximum width acrossflats

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0