

NSN 5305-01-045-4299 Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-045-4299 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.306 inches and 0.356 inches **Fastener Length:** Between 0.878 inches and 0.908 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.327 inches and 0.332 inches **Shoulder Diameter:** 0.217 inches first shoulder and 0.218 inches first shoulder **Shoulder Length:** 0.502 inches first shoulder and 0.530 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Shoulder Shape:

Round first shoulder

Special Features:

Socket drive recess in thd end 0.079 in. Min, 0.080 in. Maximum width across fats

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-045-4299

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0