NSN 5305-01-045-5609



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-045-5609 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.306 inches and 0.356 inches **Fastener Length:** Between 0.691 inches and 0.721 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.376 inches and 0.385 inches **Shoulder Diameter:** 0.2177 inches first shoulder and 0.2182 inches first shoulder **Shoulder Length:** 0.298 inches first shoulder and 0.318 inches first shoulder **Internal Drive Style:** High-torque **End Application:** Fms - aircraft, hornet f/a-18; aircraft, eagle f-15; aircraft, hornet f/a-18; aircraft, harrier av-8b **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Internal hexagon socket in threaded end 0.0791 in. Min and 0.0806 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Demilitarization:

No

Unit Of Measure:

NSN 5305-01-045-5609 Shoulder Screw - Page 2 of 2



Fiig:

A003b0