NSN 5305-01-045-8669

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-045-8669 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.215 inches **Fastener Length:** 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 48600 pounds per square inch **Screw Material:** Stainless steel **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Special Features:** Altered nas1635-08-10 **Test Data Document:** 98230-0n088857-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization:

NSN 5305-01-045-8669

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072 spec.