NSN 5305-01-045-9634

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-045-9634 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.372 inches and 0.422 inches **Fastener Length:** Between 0.820 inches and 0.850 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Shoulder Diameter:** 0.2802 inches first shoulder and 0.2807 inches first shoulder **Shoulder Length:** 0.333 inches first shoulder and 0.353 inches first shoulder **Internal Drive Style:** High-torque **End Application:** Fms - aircraft, hornet f/a-18; aircraft, eagle f-15; aircraft, hornet f/a-18; aircraft, harrier av-8b **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Internal hexagon socket in thread end 0.0947 in. Min and 0.0967 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-045-9634 Shoulder Screw - Page 2 of 2



Fiig:

A003b0