## NSN 5305-01-046-0716

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-046-0716 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.306 inches and 0.356 inches **Fastener Length:** Between 1.191 inches and 1.221 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.338 inches and 0.381 inches **Shoulder Diameter:** 0.2802 inches first shoulder and 0.2807 inches first shoulder **Shoulder Length:** 0.798 inches first shoulder and 0.818 inches first shoulder **Internal Drive Style:** High-torque **End Application:** F414 engine (f/a-18 f & g); f/a-18 hornet **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Socket drive recess in thread end 0.0947 in. Min and 0.0967 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

## NSN 5305-01-046-0716

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0