
NSN 5305-01-046-0720

Shoulder Screw - Page 1 of 2

3a

28





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.372 inches and 0.422 inches Fastener Length: Between 0.570 inches and 0.600 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.456 inches and 0.508 inches Shoulder Diameter: 0.2177 inches first shoulder and 0.2182 inches first shoulder Shoulder Length: 0.083 inches first shoulder and 0.103 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Socket drive recess in thread end 0.0947 in min and 0.0967 in. Maximum width across flats Material: Steel comp xm-13 Material Specification: Ams5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

NSN 5305-01-046-0720

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

