NSN 5305-01-046-1184

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-046-1184 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.165 inches and 0.195 inches **Fastener Length:** Between 0.708 inches and 0.738 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** 0.105 inches **First Diameter From Head:** Between 0.513 inches and 0.573 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.143 inches and 0.147 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 41.0 rockwell c and 45.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 416 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-046-1184

Externally Relieved Body Screw - Page 2 of 2



em			

No

Fiig:

A003b0