NSN 5305-01-046-2080

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-046-2080

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.491 inches and 0.541 inches
Fastener Length:
Between 0.939 inches and 0.969 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.510 inches and 0.564 inches
Shoulder Diameter:
0.389 inches first shoulder and 0.390 inches first shoulder
Shoulder Length:
0.396 inches first shoulder and 0.419 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Special Features:
Socket drive recessin thread end 0.158 in. Min and 0.162 in. Maximum width across flats
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-046-2080

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0