

View Online at <https://aerobasegroup.com/nsn/5305-01-046-3237>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.151 inches and 0.193 inches

**Fastener Length:**

Between 0.453 inches and 0.485 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**First Diameter From Head:**

Between 0.096 inches and 0.102 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.292 inches and 0.302 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Color green federal standard 595 color no. X24087

**Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

**Surface Treatment:**

Passivate or paint

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0