NSN 5305-01-046-3343

Shoulder Screw - Page 1 of 2

3a

24





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.442 inches and 0.492 inches Fastener Length: Between 0.952 inches and 0.982 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.472 inches Shoulder Diameter: 0.327 inches first shoulder and 0.328 inches first shoulder Shoulder Length: 0.460 inches first shoulder and 0.484 inches first shoulder **Internal Drive Style:** High-torque **End Application:** Aircraft, eagle f-15; harrier **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Socket drive recess in thread end 0.127 in. Min and 0.130 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5305-01-046-3343

Shoulder Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

