NSN 5305-01-046-3888

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-046-3888 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.171 inches and 1.295 inches **Fastener Length:** Between 1.313 inches and 1.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.332 inches and 0.385 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response Color: Black **Thread Series Designator:** Unjf **Specification Data:** 80205-nas514 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0

NSN 5305-01-046-3888

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.