## NSN 5305-01-046-3975

Shoulder Screw - Page 1 of 2

3a

24

---

View Online at https://aerobasegroup.com/nsn/5305-01-046-3975



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.442 inches and 0.492 inches Fastener Length: Between 1.514 inches and 1.544 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.472 inches Shoulder Diameter: 0.327 inches first shoulder and 0.328 inches first shoulder Shoulder Length: 1.022 inches first shoulder and 1.046 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Socket drive recess in thread end 0.127 in. Min and 0.130 in. Maximum width across flats Material: Steel comp xm-13 Material Specification: Ams5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

## NSN 5305-01-046-3975

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

