NSN 5305-01-046-5293

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-046-5293 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.178 inches and 0.198 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.072 inches and 0.076 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.271 inches and 0.322 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

No

A003b0