## NSN 5305-01-046-5442

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-046-5442

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.441 inches and 0.508 inches
Fastener Length:
Between 0.701 inches and 0.748 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.461 inches and 0.507 inches
Shoulder Diameter:
0.342 inches first shoulder and 0.343 inches first shoulder
Shoulder Length:
0.240 inches first shoulder and 0.260 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Special Features:
Internal hexagon socket 0.127 in. Min and 0.130 in. Maximum width across flats, 0.160 in. Deep in thread end
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-046-5442

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0