NSN 5305-01-046-5447



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-046-5447 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.491 inches and 0.541 inches **Fastener Length:** Between 1.251 inches and 1.281 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.510 inches and 0.564 inches **Shoulder Diameter:** 0.389 inches first shoulder and 0.390 inches first shoulder **Shoulder Length:** 0.708 inches first shoulder and 0.731 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Socket drive recesss in thread end 0.158 in. Min and 0.162 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-046-5447

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0