NSN 5305-01-046-8033



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-046-8033 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.442 inches and 0.492 inches **Fastener Length:** Between 1.265 inches and 1.294 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.477 inches **Shoulder Diameter:** 0.3271 inches first shoulder and 0.3276 inches first shoulder **Shoulder Length:** 0.802 inches first shoulder and 0.822 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Socket drive recess in thread end 0.127 inch min and 0.130 inch maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-046-8033

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0