## NSN 5305-01-046-8040



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-046-8040 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.306 inches and 0.356 inches **Fastener Length:** Between 1.128 inches and 1.158 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.327 inches and 0.332 inches **Shoulder Diameter:** 0.2802 inches first shoulder and 0.2807 inches first shoulder **Shoulder Length:** 0.746 inches first shoulder and 0.762 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Socket drive recess in thread end 0.0791 in. Min and 0.0806 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** 

Ams5629 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5305-01-046-8040

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0