## NSN 5305-01-047-0352

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-047-0352



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.360 inches and 0.454 inches Fastener Length: Between 0.423 inches and 0.454 inches **Head Style:** Pan **Head Diameter:** Between 0.265 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches Locking Feature: Patch or pellet or strip **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 Locking Feature Material: Plastic polyamide **Screw Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:**

No

## **NSN 5305-01-047-0352** Machine Screw - Page 2 of 2

Fiig: A500d0

