NSN 5305-01-047-0482

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-047-0482 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.516 inches **Fastener Length:** Between 1.312 inches and 1.343 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.542 inches and 0.596 inches **Grip Diameter:** Between 0.4062 inches and 0.4067 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a
Unit Of Measure:

NSN 5305-01-047-0482

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0