# NSN 5305-01-047-1859

Panel Screw Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-047-1859



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.855 inches and 0.865 inches

## Head Style:

Flat chamfer

#### **Head Diameter:**

Between 0.367 inches and 0.376 inches

#### **Head Height:**

0.172 inches

## Internal Drive Style:

Hexagon

## Material Accommodated Thickness:

Between 0.031 inches and 0.062 inches

**Thread Diameter:** 

0.250 inches

## Width Across Flats:

Between 0.1875 inches and 0.1895 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 304 stand-off

## **Material Specification:**

Mil-s-23195 military specification single material response stand-off

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0

## NSN 5305-01-047-1859

Panel Screw Assembly - Page 2 of 2

## Mil-std (military Standard):

Mil-s-23195 spec.

