## NSN 5305-01-047-4000

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-047-4000

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.290 inches and 0.357 inches
Fastener Length:
Between 1.425 inches and 1.472 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.451 inches and 0.507 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 1.115 inches and 1.472 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches grip
Material:
Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740
Material Specification:
-1I-s-5000 military specification 1st material response or -1I-s-5000 military specification 2nd material response or -1I-s-5626 military
specification 3rd material response or -1I-s-6049 military specification 4th material response
Thread Series Designator:
Unjf
Specification Data:
86823-51b334 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-047-4000

Close Tolerance Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

spec.