

View Online at <https://aerobasegroup.com/nsn/5305-01-047-6233>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.050 inches and 0.082 inches

Fastener Length:

0.100 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.099 inches and 0.119 inches

Head Height:

Between 0.018 inches and 0.025 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Countersink Angle:

811.0 degrees

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0