

View Online at <https://aerobasegroup.com/nsn/5305-01-047-6248>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.278 inches and 0.328 inches

Fastener Length:

Between 4.356 inches and 4.376 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.126 inches and 0.141 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.2487 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Slot

End Application:

Spec item

Thread Diameter:

0.250 inches

Grip Length:

Between 3.937 inches and 3.953 inches

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.260 inches first hole and 4.280 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0