

View Online at <https://aerobasegroup.com/nsn/5305-01-047-7811>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.440 inches and 0.496 inches

Fastener Length:

Between 0.500 inches and 0.531 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.105 inches and 0.119 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

82.0 degrees

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

Screw Surface Treatment:

Passivate

Thread Series Designator:

Unf

Specification Or Standard:

3 type and 2c style and 1 design

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0