## NSN 5305-01-047-8823

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-047-8823 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.349 inches and 0.416 inches **Fastener Length:** Between 1.734 inches and 1.781 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.469 inches and 0.474 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unjf **Specification Data:** 76823-51b581 professional/industrial association standard Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5305-01-047-8823

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0