

View Online at <https://aerobasegroup.com/nsn/5305-01-048-1138>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.708 inches and 0.738 inches

Fastener Length:

1.758 inches

Head Style:

Fillister

Head Diameter:

0.865 inches

Head Height:

0.470 inches

Shoulder Diameter:

0.748 inches first shoulder and 0.750 inches first shoulder

Shoulder Length:

0.555 inches second shoulder

Shank Unthreaded Hole Diameter:

0.093 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.437 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

32.0 rockwell c and 37.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.148 inches first hole

Shoulder Shape:

Round all shoulders

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 3, class 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.