

View Online at <https://aerobasegroup.com/nsn/5305-01-048-6098>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.427 inches and 0.494 inches

**Fastener Length:**

Between 1.312 inches and 1.359 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.662 inches and 0.668 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.096 inches first hole and 0.116 inches first hole

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 0.865 inches and 0.885 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.204 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate or cadmium

**Thread Series Designator:**

Unjf

**Specification Data:**

76823-51b58 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0