

View Online at <https://aerobasegroup.com/nsn/5305-01-049-0624>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.381 inches and 0.447 inches

Fastener Length:

Between 1.266 inches and 1.312 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.327 inches and 0.385 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Internal Drive Style:

Cross recess type 1

End Application:

Helo, elect countermeasures; e-3a awacs; blackhawk helicopter

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4037 or steel comp 8630

Material Specification:

Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.