## NSN 5305-01-049-1251

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-049-1251



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.246 inches and 0.323 inches Fastener Length: Between 1.573 inches and 1.620 inches **Head Style:** Pan **Head Diameter:** Between 0.361 inches and 0.381 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 1.297 inches and 1.327 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 86823-51b221 professional/industrial association standard Shelf Life:

N/a

## NSN 5305-01-049-1251

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

