

View Online at <https://aerobasegroup.com/nsn/5305-01-049-2163>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.148 inches and 0.250 inches

**Fastener Length:**

Between 0.219 inches and 0.250 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.473 inches and 0.492 inches

**Head Height:**

Between 0.130 inches and 0.144 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

**Screw Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0