

View Online at <https://aerobasegroup.com/nsn/5305-01-049-4012>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.750 inches

**Fastener Length:**

Between 2.406 inches and 2.500 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.250 inches and 0.270 inches

**Head Height:**

Between 0.102 inches and 0.113 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

**Screw Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 4s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0