## NSN 5305-01-049-9118

Machine Screw - Page 1 of 1

**Demilitarization:** 

No Fiig: A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-049-9118 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.495 inches and 0.562 inches **Fastener Length:** Between 0.531 inches and 0.562 inches **Head Style:** Fillister **Head Diameter:** Between 0.124 inches and 0.140 inches **Head Height:** Between 0.053 inches and 0.062 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316 or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 **Screw Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**