## NSN 5305-01-050-1510

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-050-1510 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.756 inches and 0.806 inches **Fastener Length:** Between 1.454 inches and 1.484 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.747 inches and 0.752 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Dry film lubricant p.S. 18021 cl 1 Material: Titanium alloy **Thread Series Designator:** Unjf **Specification Data:** 76301-st3-466 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-050-1510

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0