NSN 5305-01-050-4308



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-050-4308 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.306 inches and 0.356 inches **Fastener Length:** Between 1.504 inches and 1.534 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.338 inches and 0.381 inches **Shoulder Diameter:** 0.2021 inches first shoulder and 0.2026 inches first shoulder **Shoulder Length:** 1.105 inches first shoulder and 1.125 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Socket drive recess in thread end 0.0791 in. Min and 0.0806 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

__

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-050-4308

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0