NSN 5305-01-050-4992

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-050-4992

| Thread Class: | |
|--|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.631 inches and 0.681 inches | |
| Fastener Length: | |
| Between 1.266 inches and 1.296 inches | |
| Head Style: | |
| Oval countersunk | |
| Head Diameter: | |
| Between 0.662 inches and 0.668 inches | |
| Grip Diameter: | |
| Between 0.4365 inches and 0.4370 inches | |
| Internal Drive Style: | |
| High-torque | |
| Thread Diameter: | |
| 0.438 inches | |
| Grip Length: | |
| Between 0.615 inches and 0.635 inches | |
| Thready Qty Per Inch (tpi): | |
| 20 | |
| Min. Tensile Strength (psi): | |
| 160000 pounds per square inch | |
| Countersink Angle: | |
| 100.0 degrees | |
| Surface Finish: | |
| 32.0 microinches top of head | |
| Special Features: | |
| Dry film lubricant p.S. 18021 cl 1 | |
| Material: | |
| | |
| Thread Series Designator: | |
| Unjf | |
| Specification Data: | |
| 76301-st3-466 professional/industrial association standard | |
| Shelf Life: | |
| | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 5305-01-050-4992

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

