NSN 5305-01-050-9002

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-050-9002 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.503 inches and 0.553 inches **Fastener Length:** Between 1.513 inches and 1.543 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.825 inches and 0.890 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.438 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 22000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-050-9002

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0