NSN 5305-01-050-9642

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-050-9642 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.500 inches **Fastener Length:** Between 1.690 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life:

Unit Of Measure:

N/a

NSN 5305-01-050-9642

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.