NSN 5305-01-051-0626

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-051-0626 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.657 inches and 0.750 inches **Fastener Length:** Between 0.719 inches and 0.750 inches

Head Diameter: Between 0.208 inches and 0.226 inches **Head Height:** Between 0.089 inches and 0.096 inches

Hole Diameter: 0.046 inches

Internal Drive Style:

Slot

Head Style: Fillister

Thread Diameter:

0.138 inches

Hole Quantity:

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 303se or steel comp 304l or steel comp 302b or steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel co comp 316 or steel comp 384

Head Surface Treatment:

Enamel

Screw Surface Treatment:

Passivate

Head Hole Configuration Style:

Round longitudinal hole

Special Features:

Color black federal standard 595 no. 27038

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-051-0626

Machine Screw - Page 2 of 2



em			

No

Fiig:

A500d0