## NSN 5305-01-051-5506

**Thread Class:** 

Right-hand **Thread Length:**0.363 inches

**Thread Direction:** 

Fastener Length:

Between 0.786 inches and 0.816 inches

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-051-5506

Head Style:					
Flat countersunk					
Head Diameter:					
Between 0.305 inches and 0.358 inches					
Grip Diameter:					
Between 0.1885 inches and 0.1895 inches					
Single Shear Strength:					
132000 pounds per square inch					
Internal Drive Style:					
Offset cruciform (torque set)					
Thread Diameter:					
0.190 inches					
Grip Length:					
Between 0.428 inches and 0.448 inches					
Thready Qty Per Inch (tpi):					
32					
Min. Tensile Strength (psi):					
220000 pounds per square inch					
Hardness Rating:					
46.0 rockwell c and 49.0 rockwell c					
Countersink Angle:					
Between 99.0 degrees and 101.0 degrees					
Surface Finish:					
32.0 microinches threads					
Material:					
Steel comp h11					
Material Specification:					
Ams 6487 assn standard single material response					
Surface Treatment:					
Surface Treatment: Cadmium and chromate					
Cadmium and chromate					
Cadmium and chromate Surface Treatment Specification:					
Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2 assn standard single treatment response					
Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2 assn standard single treatment response  Thread Series Designator:					

## NSN 5305-01-051-5506

Close Tolerance Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0