## NSN 5305-01-051-8022

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-051-8022 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.359 inches **Fastener Length:** Between 0.468 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.296 inches **Secondary Washer Outside Diameter:** Between 0.307 inches and 0.317 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.040 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material: Steel comp 430 or steel comp 303 or stainless steel or steel comp 301 or steel comp 302 or steel comp 304 or steel comp 316 **Surface Treatment: Passivate** 

Unc

**Thread Series Designator:** 

## NSN 5305-01-051-8022

Assembled Washer Screw - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0