

View Online at <https://aerobasegroup.com/nsn/5305-01-052-1187>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 2.750 inches and 3.107 inches

**Fastener Length:**

Between 3.562 inches and 3.750 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.749 inches and 0.813 inches

**Width Between Flats:**

Between 1.812 inches and 1.875 inches

**Thread Diameter:**

1.250 inches

**Thready Qty Per Inch (tpi):**

7

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Hardness Rating:**

74.0 rockwell b

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0