

View Online at <https://aerobasegroup.com/nsn/5305-01-052-2395>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.170 inches and 0.280 inches

Fastener Length:

Between 0.220 inches and 0.280 inches

Head Style:

Pan

Head Diameter:

Between 0.228 inches and 0.238 inches

Head Height:

Between 0.075 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

Screw Surface Treatment:

Passivate

Special Features:

Furnished with o-ring, bearing surface of head grooved for o-ring

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0