## NSN 5305-01-052-2404

Socket Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-052-2404



2a  Fyread Direction: Right-hand  Fyread Length: Between 0.149 inches and 0.250 inches  Fastener Length: Between 0.220 inches and 0.250 inches  Fact Style: Pan  Head Diameter: Between 0.473 inches and 0.492 inches Head Height: Between 0.142 inches and 0.175 inches  Locking Feature: Patch threads  Internal Drive Style: Cross recess type 1  Thread Diameter: 0.250 inches  Fyread Ydty Per Inch (tpi): 28  Special Features: Color black MateriaI: Stainless steel  Surface Treatment: Oxide  Thread Series Designator: Unf  Sheff Life: Na  Cine Measure:	Thread Class:
Right-hand   Thread Length:   Between 0.149 inches and 0.250 inches   Fastener Length:   Between 0.220 inches and 0.250 inches   Head Style:   Pan   Head Diameter:   Between 0.473 inches and 0.492 inches   Head Height:   Between 0.162 inches and 0.175 inches   Locking Feature:   Patch threads   Internal Drive Style:   Cross recess type 1   Thread Diameter:   0.250 inches   Thread Yely Per Inch (tpi):   28   Special Features:   Color black   Material:   Stainless steel   Surface Treatment:   Oxide   Thread Series Designator:   Unf   Sheff Life:   Na   Life:   Na   Pailitarization:   No   Fig:	2a
Thread Length:         Between 0.149 inches and 0.250 inches         Fastener Length:         Between 0.220 inches and 0.250 inches         Head Style:         Pan         Head Diameter:         Between 0.473 inches and 0.492 inches         Head Height:         Between 0.162 inches and 0.175 inches         Locking Feature:         Patch threads         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Thready Qty Per Inch (tpi):         28         Special Features:         Color black         Material:         Stainless steel         Surface Treatment:         Oxide         Thread Series Designator:         Unf         Sheft Life:         Na         Dint Of Measure:         Camere:         Dint Of Measure:         Totation:         No         Fig:	Thread Direction:
Between 0.149 inches and 0.250 inchesFastener Length:Between 0.220 inches and 0.250 inchesHead Style:PanHead Diameter:Between 0.473 inches and 0.492 inchesHead Height:Between 0.162 inches and 0.175 inchesLocking Feature:Patch threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.250 inchesThread Diameter:0.250 inchesSpecial Features:Color blackMaterial:Stainless steelSurface Treatment:OxideThread Series Designator:UnfShelf Life:N/aDin of Measure:-Demilitarization:NoFig:	Right-hand
Fastener Length:Between 0.220 inches and 0.250 inchesHead Style:PanHead Diameter:Between 0.473 inches and 0.492 inchesHead Height:Between 0.162 inches and 0.175 inchesLocking Feature:Patch threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.250 inchesThread Diameter:0.250 inchesSpecial Features:Color blackMaterial:Stainless steelSurface Treatment:OxideThread Series Designator:UnfShelf Life:N/aDin Giameter:NaDin Giameter:NaDin Strike Treatment:Din Strike Series Designator:UnfShelf Life:NaTreatFig:Stig:	Thread Length:
Between 0.220 inches and 0.250 inches         Head Style:         Pan         Head Diameter:         Between 0.473 inches and 0.492 inches         Head Height:         Between 0.162 inches and 0.175 inches         Locking Feature:         Patch threads         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Thready Qty Per Inch (tpi):         28         Special Features:         Color black         Material:         Stainless steel         Surface Treatment:         Oxide         Thread Series Designator:         Unf         Shelf Life:         N/a         Path Life:         N/a         Femilitarization:         No         Fig:	Between 0.149 inches and 0.250 inches
Head Style: Pan Head Diameter: Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Head Height: Between 0.162 inches and 0.175 inches Locking Feature: Patch threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thread Y Per Inch (tpi): 28 Special Features: Color black Material: Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Fastener Length:
PanHead Diameter:Between 0.473 inches and 0.492 inchesHead Height:Between 0.162 inches and 0.175 inchesLocking Feature:Patch threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Special Features:Color blackMaterial:Stainless steelSurface Treatment:OxideThread Series Designator:UnfShelf Life:N/aDint of Measure:-Penilitarization:NoFig:	Between 0.220 inches and 0.250 inches
Head Diameter: Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Locking Feature: Patch threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Special Features: Color black Material: Stainless steel Surface Treatment: Color black Intread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Head Style:
Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Locking Feature: Patch threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Special Features: Color black Material: Stainless steel Surface Treatment: Coxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Pan
Head Height: Between 0.162 inches and 0.175 inches Locking Feature: Patch threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Special Features: Color black Material: Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Head Diameter:
Between 0.162 inches and 0.175 inches Locking Feature: Patch threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Special Features: Color black Material: Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Between 0.473 inches and 0.492 inches
Locking Feature:Patch threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Special Features:Color blackMaterial:Stainless steelSurface Treatment:OxideThread Series Designator:UnfShelf Life:N/aDemilitarization:NoFig:	Head Height:
Patch threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Special Features: Color black Material: Color black Material: Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.162 inches and 0.175 inches
Internal Drive Style: Cross recess type 1 Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Special Features: Color black Color black Material: Color black Material: Color black Material: Stainless steel Surface Treatment: Color black Stafface Treatment: Color black Material: Stafface Treatment: Color black Stafface Treatment: Color black Stafface Treatment: Color black Stafface Treatment: Color black Color black Co	Locking Feature:
Cross recess type 1  Thread Diameter:  0.250 inches  Thready Qty Per Inch (tpi):  28  Special Features:  Color black  Material:  Color black  Material:  Stainless steel  Stainless steel  Surface Treatment:  Oxide  Thread Series Designator:  Unf  Shelf Life: N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Patch threads
Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Special Features: Color black Material: Color black Material: Stainless steel Stainless steel Stainless steel Chread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Internal Drive Style:
0.250 inches Thready Qty Per Inch (tpi): 28 Special Features: Color black Material: Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Cross recess type 1
Thready Qty Per Inch (tpi): 28 Special Features: Color black Material: Stainless steel Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thread Diameter:
28 Special Features: Color black Material: Stainless steel Striace Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	0.250 inches
Special Features: Color black Material: Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thready Qty Per Inch (tpi):
Color black Material: Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	28
Material:Stainless steelSurface Treatment:OxideThread Series Designator:UnfShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Special Features:
Stainless steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Color black
Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Material:
Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Stainless steel
Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Surface Treatment:
Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Oxide
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization: No Fiig:	Unf
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
4003b0	Fiig:
100000	A003b0